



## GLITFLEX

### PRODUCT DESCRIPTION:

Thermal bonding film with glitter effect, suitable for heat transfer applications to cotton, polyester and mixed fabrics. Perfectly suitable for the creation of medium- and large-sized logos and images.

### FILM FEATURES:

- Film thickness (Indicative value)  
**330 µm**

### LINER:

- 100-µm polyester backing paper.

### APPLICATION GUIDE FOR FLEX:

- Good adhesion to cotton, polyester and mixed fabrics.

*Carry out a test to check the resistance of the fabric to the press temperature and the compatibility of the flex film with the cloth.*

Cutting and weeding



- Cut the mirror image with the plotter through the protector.
- Using a blade in good shape, at a 45-degree angle;
- Applying high pressure;
- Cutting size: large-sized logos.
- Weed slowly after cutting.



Pressing temperature  
**160 °C (320 °F)**



Pressing duration  
**10 seconds**

- Carefully remove the transfer tape while the film is still



Protector removal:  
**hot**



Washing temperature  
**with a maximum of 40 °C (104 °F)**



Washing conditions  
**Turn your garment inside out for washing and use laundry products without chlorine bleach.**



Drying conditions  
**Tumble drying is prohibited.**



Ironing conditions  
**Iron the textile inside out or protect the flex film with a pressing cloth, at low temperature, without using steam.**

- For more information on the application method of GLITTER, please refer to the Application Guide on the «Professionals» pages, on our website [www.hexis-graphics.com](http://www.hexis-graphics.com).

### STORAGE:



Storage period before use  
**1 year**



Storage temperature  
**+15 °C to +25 °C (+59 °F to +77 °F)**



Relative humidity during storage  
**with relative humidity between 30 % and 70 %**



Storage method before use  
**in its unopened original packaging**

### NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website [www.hexis-graphics.com](http://www.hexis-graphics.com).