

Uniktryk DTF Transfer

Produktionsfilm til tekstiltransfer · DTF-C-PEEL



Illustration af transferfilm; ikke en farveprøve.

DOKUMENTEREDE SYMBOLER

Denne variant har ingen af katalogets generelle symboler registreret her. Se de konkrete egenskaber nedenfor og det originale datablad.

Materialets egne egenskaber: DTF · kold peeling · 80 µm PET · Kombinationstjek

Sådan passer du på dit Uniktryk

01 Det færdige tryk består også af blæk og transferpulver. Pleje og vasketemperatur skal derfor fastlægges for den konkrete kombination.

02 Følg ordrebekræftelsens pleje og tekstilets etiket. Indtil kombinationen er kontrolleret: undgå vask, varme og kemisk behandling af trykket.

03 Produktionsbæreren fjernes under fremstillingen og følger ikke det færdige tøj. Kontakt os, hvis den ordrespecifikke pleje mangler.

Den mest skånsomme begrænsning på tøjets etiket eller i den konkrete produktkombination gælder. Kontakt os ved skader; undlad selv at varme eller lime.

Materiale, egenskaber og ansvarligt valg

DTF-C-PEEL er en produktionsbærer til kold peeling. Blæk, pulver og tekstil kontrolleres samlet. Ingen generel vasketemperatur eller certifikat overføres fra bærerfilmen til sluttrykket.

PET-transferfilm til produktion, ikke KRAFT- eller PE-liner.

Før produktion kontrollerer Uniktryk den præcise reference, underlag, materialekombination og monteringsmetode. Følg den konkrete pleje. Symboler er ikke en generel garanti eller tilladelse til andre anvendelser. Kilde: katalog 2026, trykt side 26, samt det vedlagte datablad.

Producentens CSR-temaer: Miljøpåvirkning · Etik og lokalsamfund · Ansvarlig innovation · Arbejdsvilkår.

Temaerne er virksomhedsindsatser, ikke fire produktcertifikater. Målet om 55 % lavere GHG-udledning i 2050 er producentens fremtidige mål, ikke dette produkts dokumenterede klimaaftryk. Kilde: katalog 2026, trykte sider 18-21.



Scan til den aktuelle vejledning

De følgende sider er producentens originale tekniske datablad. Produktkoder og kildeangivelser er bevaret, så materialet kan spores. Vejledningen begrænser ikke dine lovbestemte rettigheder.



DTF-C-PEEL

PRODUCT DESCRIPTION:

80-µm, transparent PET film, intended for printing/transferring graphics using the digital DTF (Direct To Film) printing method.

FILM FEATURES:

- Film thickness (Indicative value)
80 µm

APPLICATION GUIDE FOR FLEX:

Before using the DTF film for the first time, it is advisable to carry out a test of all processing stages, comparable to the production conditions, in order to check the results obtained. Depending on the result, the parameters for film processing must be adjusted.

- Maximum film operation temperature: 165 °C (329 °F).
- Print the visual in mirror mode on the matt side of the film (treated side).
Please refer to the inks' and printers' operating instructions.
- Apply hot-melt adhesive to the graphic, remove any excess adhesive and heat the film + adhesive.
Please refer to the hot-melt adhesive's operating instructions.
- Transfer the graphic onto a compatible textile.
Refer to the inks' and hot-melt adhesives' operating instructions before carrying out the transfer.
- Remove the DTF-C-PEEL film when it is cold.

STORAGE:



Storage period before use
1 year



Storage temperature
+15 °C to +25 °C (+59 °F to +77 °F)



Relative humidity during storage
with relative humidity between 30 % and 70 %



Storage method before use
in its unopened original packaging

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. The measuring methods for the standards quoted above served as the basis for the development of our own measuring methods, which are available on request. Please feel free to contact us to get the latest instructions in use. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.