

Uniktryk Print 5S

Fuldfarvet mat tekstilprint · UFLEX5S



DOKUMENTEREDE SYMBOLER



Mat overflade



Eco-solvent-blæk



Solvent-blæk



Latex-blæk

Producentens materialebillede; vejledende farve og finish.

Materialets egne egenskaber: SOLV · ECO-S · LATEX · 60 °C maks. · OEKO-TEX oplyst

Sådan passer du på dit Uniktryk

01 Vent mindst 24 timer før første vask; en uge anbefales for bedre blækholdbarhed.

02 Vask på vrangen ved højst 60 °C, hvis tøjet tillader det. Ingen klorblegning, skyllemiddel eller tørretumbling.

03 Lufterør. Stryg på vrangen, aldrig direkte på trykket. Brug på Softshell er ikke godkendt; andre tekstiler skal prøves først.

Den mest skånsomme begrænsning på tøjets etiket eller i den konkrete produktkombination gælder. Kontakt os ved skader; undlad selv at varme eller lime.

Materiale, egenskaber og ansvarligt valg

PU-film fra vandbaseret emulsion uden DMF eller lignende opløsningsmidler. OEKO-TEX STANDARD 100 er oplyst for materialet. Printkompatibilitet er ikke det samme som HP Latex-certificering.

PET/polyesterliner. Ikke KRAFT- eller PE-liner.

M: Mat beskriver udseendet. Det betyder ikke, at folien tåler polering. SOLV: Kompatibel med solventbaseret blæk. Ikke en renseanvisning med opløsningsmiddel. ECO-S: Kompatibel med den angivne blæktype. Betegnelsen er ikke en miljøcertificering. LATEX: Blækkompatibilitet er ikke det samme som særskilt HP Latex-certificering.

Før produktion kontrollerer Uniktryk den præcise reference, underlag, materialekombination og monteringsmetode. Følg den konkrete pleje. Symboler er ikke en generel garanti eller tilladelse til andre anvendelser. Kilde: katalog 2026, trykt side 26, samt det vedlagte datablad.

Producentens CSR-temaer: Miljøpåvirkning · Etik og lokalsamfund · Ansvarlig innovation · Arbejdsvilkår.

Temaerne er virksomhedsindsatser, ikke fire produktcertifikater. Målet om 55 % lavere GHG-udledning i 2050 er producentens fremtidige mål, ikke dette produkts dokumenterede klimaaftryk. Kilde: katalog 2026, trykte sider 18-21.



Scan til den aktuelle vejledning

De følgende sider er producentens originale tekniske datablad. Produktkoder og kildeangivelser er bevaret, så materialet kan spores. Vejledningen begrænser ikke dine lovbestemte rettigheder.



UFLEX5S



WHITE



PRODUCT DESCRIPTION:

80-µm, adhesive-coated polyurethane film, made from a water-based emulsion, which is free of DMF or similar solvents. Opaque white, thin film, recommended for applications to cotton and polyester textiles (except Softshell). Especially adapted for the creation of letterings, logos or small images. Matt surface finish.

FILM FEATURES:

- Thickness

(Indicative value)

80 µm

LINER:

- 105-µm polyester backing paper.

APPLICATION GUIDE FOR FLEX:

- Good adhesion to cotton and polyester.
- Do not use the UFLEX5S film on Softshell fabrics.

For any other type of textile, carry out a test to check the resistance of the fabric to the press temperature and the compatibility of the UFLEX5S film with the cloth.

- Print the image in positive mode.



Cutting and weeding

Cut and weed the image.

Minimum cutting size (unprinted areas or perfectly dry, printed areas): 0,6 cm (0.24 in.) (height of letters).

Carry out the transfer using the transfer film HEX860:
Apply the tape to the UFLEX5S using a squeegee, pressing hard.



Prerequisites

It is preferable to apply the film to previously washed fabrics.

- Preheat press and textile prior to application.



Pressing temperature

on cotton: 140 °C (284 °F)

on polyester: 130 °C (266 °F)



Pressing duration

5 seconds

In any case, always perform a preliminary trial so as to best adjust the pressing conditions before carrying out large series.



Pressing strength

moderate pressure



Carefully remove the transfer tape while the film is still: hot



Repressing duration

5 seconds

Rest time before washing

After pressing, wait for at least 24 hours before washing the garment. For better ink durability, it is preferable to wait for one week before carrying out the first washing.



Washing temperature

with a maximum of 60 °C (140 °F)



Washing conditions

Use laundry products without chlorine bleach.



Drying conditions

Tumble drying is prohibited.



Ironing conditions

Iron your garment inside out.

OPERATING RECOMMENDATIONS:

- The use of softeners is not recommended since it can cause an alteration of the flex film adhesion to the fabric.
- For more information on the application method of the UFLEX5S film, please refer to the PRINTFLEX Application Guide available under the «Professionals» heading, in the «Films for textile» category on our website www.hexis-graphics.com.

STORAGE:



Storage period before use

1 year



Storage temperature

+15 °C to +25 °C (+59 °F to +77 °F)



Relative humidity during storage

with relative humidity between 30 % and 70 %



Storage method before use

in its unopened original packaging

**LABELLING PRODUCT:**

Oeko-Tex® Standard 100 label

**STANDARD
100**CQ 1126/1
IFTH**NOTES:**

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.

